

4200

General Purpose 2D Area Imager



Features

Ergonomic Design - Linear imager performance, with the versatility of area imaging all in a small, sleek housing.

Omni-directional reading of 1D, PDF417, MicroPDF417, Postal, Matrix, and EAN•UCC Composite codes, and OCR fonts for the easiest ever data collection.

Image Capture - Class-leading image quality and image transfer speed provide crisp images in less than one second.

Connectivity – The most popular interfaces in one model. Uses the standard Hand Held Products cable set.

Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and makes image capture applications fast and intuitive.

The 4200 area imager from Hand Held Products combines the versatility of area imaging with the speed and cost of linear scanning for retail and commercial applications. Powered by Adaptus™ Imaging Technology, the 4200 is full featured, fast, and cost effective.

Current and future manufacturing, retail, and commercial applications will involve much more than linear bar codes. EAN•UCC composite codes are beginning to appear in food stores, PDF codes are used for age verification in restricted item sales, and postal bar codes are used to sort mail. The omni-directional reading capability of the 4200 allows fast and easy reading of all these codes. Simply point and shoot. There's no need to align a scan line, or wait for a raster beam to open up.

Whether capturing a signature as proof of delivery, taking a picture for identification, or electronic data storage, image capture is an important part of current and future solutions. The Adaptus Imaging Technology powered 4200 is equipped with Hand Held Products fifth generation imaging for best-in-class image quality and image transfer speed, all at very economical prices. Image capture has become a mainstream application requirement. Trust Hand Held Products to provide the industry's best imaging.

With no moving parts, the 4200 is as durable as it is versatile. Hand Held Products has a reputation for products that are tough as nails. The 4200 is no exception, and will provide years of service at a low cost.

To learn how the 4200 can work for you, contact us at any of the locations listed on the back or visit us at www.handheld.com.

4200 Specifications

Performance

Aiming:

Green Aiming LED: 526nm ±30nm

Image: 752x480. Binary, TIFF, or JPEG output.

Working Range (from window):

4200 SR	8.3 mil Linear (.021cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	15 mil QR Code (.038cm)
Near	3.5 in. (8.9cm)	2.1 in. (5.3cm)	4.5 in. (11.4cm)	3.1 in. (7.9cm)	2.3 in. (5.8cm)	3.1 in. (7.9cm)
Far	7.6 in. (19.3cm)	13.2 in. (33.5cm)	6.2 in. (15.7cm)	9.0 in. (22.9cm)	10.2 in. (25.9cm)	8.8 in. (22.4cm)
4200 SF	7.5 mil Linear (.019cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	8.3 mil Data Matrix (.021cm)	8.3 mil QR Code (.021cm)
Near	2.5 in. (6.4cm)	2.0 in. (5.1cm)	2.8 in. (7.1cm)	2.2 in. (5.6cm)	3.4 in. (8.6cm)	3.3 in. (8.4 cm)
Far	6.5 in. (16.5cm)	8.9 in. (22.6cm)	6.0 in. (15.2cm)	7.6 in. (19.3cm)	5.7 in. (14.5cm)	5.4 in. (13.7cm)
4200 HD	5 mil Linear (.013cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	6.7 mil Data Matrix (.017cm)	6.7 mil QR Code (.017cm)
Near	2.4in. (6.1cm)	2.1 in. (5.3cm)	2.1 in. (5.3cm)	1.9 in. (4.8cm)	2.9 in. (7.4cm)	2.8 in. (7.1cm)
Far	4.3in. (10.9cm)	6.7in. (17.0cm)	5.0 in. (12.7cm)	5.8 in. (14.7cm)	4.0 in. (10.2cm)	3.9 in. (9.9cm)

Skew Angle: ±40°

Pitch Angle: ±40°

Horizontal Velocity: 4 in. (10 cm) per second

Mechanical/Electrical

Dimensions

Length: 5.5 in. (14.0 cm)

Height: 5.3 in. (13.5 cm)

Width: 2.6 in. (6.6 cm)

Weight: 4.5 oz. (127.6 g)

Housing: UL 94V0 grade

Power Requirements: 5Vdc ±10% at scanner

Current Draw (Typical)

Input	Scanning	Idle
5 V	382 mA	53 mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: +32°F to +122°F (0°C to +50°C)

Storage: -40°F to 140°F (-40°C to +60°C)

Humidity: 0 to 95%, non-condensing

Mechanical Shock: Operational after 25 drops from 4.9 ft. (1.5 m) to concrete

Ambient Light: Up to 100,000 lux (full sunlight)

ESD Protection: Functional after 100 8kV discharges

Vibration: Withstands 1G peak from 8 to 80 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, C-Tick N10410

MTBF: per MIL-HDBK-217F Ground Benign exceeds 70,000 hours

Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Code 49, and EAN•UCC Composite

Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock, and BC412*
*available to licensed users

Postal: Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)

OCR Fonts: OCR-A, OCR-B

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, TTL level RS-232, wand emulation mode, TTL level Serial Wedge.

Warranty: Two year factory warranty.

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France
Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com
Shanghai
Tel: +86 21 6361 3818
appresales@handheld.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 2178 0500
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2178 0500
lapresales@handheld.com
Mexico
Tel: +52 55 5203 2100
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.