

Specifications

Model	Aura-7700
Print Method	Thermal sensitive line dot method
Print Speed	180 mm/sec.
Print Resolution	8 dots/mm (512 dots/line)
Printing Width	Max. 72 mm (576 dots/line)
Interface	Wireless
Input Buffer	10 KB
Operating System Compatibility	Windows, OPOS
Dimension	148 mm x 199 mm x 144 mm (5.8" x 7.8" x 5.7")
Weight	1.35 kg
Color	Charcoal
LED Indicator	Printing: Green, Error: Red, Paper Out: Red
Sensor	Hood Lock, Paper Near End, Paper Out, Overheat
Safety Certification	CE: Class A; FCC: Class A
Printing Paper	
Paper type	Thermal roll paper
Paper Width	80 (or 58) mm
Paper Feed Method	Friction auto-feed
Paper Load Method	Drop-and-load
Paper Cutter	
Auto-cutter	Guillotine type to provide partial cut with 1 point at center left
Manual-cutter	Saw tooth blade
Language Support	
Language Model	Standard, European, Japan Kanji, Korean Simplified Chinese, Traditional Chinese
International Character Set	15 international character sets supported(Denmark I, Denmark II, Ex-Yugoslavia, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain, Spain II, Sweden, UK, USA)
Character Code Page	8 code pages supported
Bar Code Printing	UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128
Accessory	
Paper Guide Adaptor	Optional 58 mm paper guide adaptor
Kitchen Bell	Optional
Wall Mount Kit	Optional

** The product information and specifications are subject to change without prior notice.