

Specifications

Model	PP-5600B/5600D
Printing Function	Receipt/Journal
Print Method	Serial impact dot matrix method
Print Speed	4 lines/sec.
Print Resolution	42 columns/line (59.85 mm)
Interface	Serial (RS232C), Parallel
Input Buffer	Max. 20 KB
Operating System Compatibility	DOS, Windows, OPOS
Dimension	228 mm (L) x 158 mm (W) x 140 mm (H) (9" x 6.2" x 5.5")
Weight	1.6 kg (N.W.)/ 1.9 kg (with auto-cutter)
Color	Ivory White, Charcoal
LED Indicator	Printing: Green Error: Red Paper Out: Red
Sensor	Paper Out, Paper Near End, Overheat, Cash Drawer Opening
Safety Certification	CE: Class A; FCC: Class A
Printing Paper	
Paper type	Ordinary paper, 3-fold carbonless copy paper
Paper Width	76 mm
Paper Feed Method	Friction auto-feed
Paper Load Method	Drop-and-load
Paper Cutter	
Auto-cutter	PP-5600B: Guillotine type auto-cutter to provide partial cut with 1 point at center left
Manual-cutter	PP-5600D: Saw tooth blade manual cutter
Ink	
Ink	Ribbon Cassette (RC-200P, Purple)
Language Support	
Language Model	Standard, Baltic font, Greek, Japanese Kanji, Korean character, Russian, Simplified Chinese, Thai, Traditional Chinese
International Character Set	15 international character sets supported (Croatia, Denmark I, Denmark II, England, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain I, Spain II, Sweden, USA)
Character Code Page	5 code pages supported: USA & European PC 437, 850, 860, 863, 865
Accessory	
Kitchen Bell	Optional

** The product information and specifications are subject to change without prior notice.